

NOTES:



Current Rating:3.0AMP
 Contact Resistance:3.0milliohm Max
 Withstand Voltage:500V AC
 Insulation Resistance:1000Megohm Min
 Operation Temperature:-40°C to +105°C

Housing Material:PPA(U194V-0)

Contact Material:Brass

Contact plating:Au over Ni Plating

RECOMMENDED PCB LAYOUT
 TOLERANCE IS ±0.05






Ordering Information

3126 - 06 S XX B K00 R 1

No. of Pins per Row: 06
 Contact Plating: None Or Pin
 Insulator Color: K00(Full pin)
 Packaging: R-Tape & Reel

Gr-Cold Finish
 G1-3r/Cold
 G2-5r/Cold
 G3-10r/Cold
 G4-13r/Cold
 G5-15r/Cold
 G6-20r/Cold
 SPl-Gold Flash/Tm
 S1-3r/Cold/Tm
 S2-5r/Cold/Tm
 S3-10r/Cold/Tm
 S4-13r/Cold/Tm
 S5-15r/Cold/Tm
 S6-20r/Cold/Tm
 SPl-Tm



REV	DATE	MODIFICATION DESCRIPTION	CHANGE
A0	2012.07.20	NEW	-

OPERATION	DRAW	DATE	SCALE	PART NO.
XX	LKP	2012.07.20	1:1	3126-06SXXBK00R1
XX	CHECK	DATE	UNIT	TITLE:
XX	±0.25	DATE	mm	2.0 BOX XXP S/T H=6.55
X,XX	±0.15	DATE <td>SIZE</td> <td>SHEET</td>	SIZE	SHEET
Angle	± 3'	DATE	A4	1/1
DM	TOL	DATE	PROU.	Customer NO.

上海回峰电子科技有限公司 Shanghai Hui Feng Electronics Technology Co., Ltd	
电话: 021-67150229	传真: 021-67150251
电子邮箱: huiheng_dz@163.com	公司网址: www.huiheng-china.com